

HT3200EUV

Inkjet UV Hybrid Printer

- Kyocera Series



*Illustration purpose

Optional Models:

- **HT1600UV** Easily competent for small and medium orders
- **HT2500UV** Cost-effective choice for coils and sheets in medium size
- **HT3200UV** Smart choice for large-format high-speed hybrid printing
- **HT3200EUV** Brand new exterior design, suitable for wide-format hybrid printing
- **HT5200UV** Super large-format hybrid printing in one

Range of Large Format Printers with high speed drop on demand piezo inkjet technology.
Outstanding Performance:



Automatic Negative
Pressure System



Automatic Height
Measurement System



Adjustable UV
Curing Power



Sensitive Collision Avoidance
Device for the Carriage



Automatic Alignment
System (HT3200)



Adjustable Suction Area



Optional Anti-Static Bar



Positioning Rod



Integrated Software Functions
(Require ADP / Computer)



High-Quality Imported
Components

UV Hybrid Inkjet Printer - Kyocera Series								
Model		HT1600UV	HT2500UV	HT3200UV		HT3200EUV	HT5200UV	
Printing Information								
Printhead		Kyocera						
Number of Printhead		2-4 Pcs (1-Row)	3-4 Pcs (1-Row)	4-8 Pcs (2-Row)	4-15 Pcs (3-Row)	4-10 Pcs (Symmetrical 2-row)	2-15 Pcs- (3-Row)	2-15 Pcs (Symmetrical 3-row)
Resolution		1200*1200 DPI				363*3600 DPI	1210*1200 DPI	363*3600 DPI
Production Mode	Draft	44 m²/h	55 m²/h	129 m²/h	175 m²/h	142 m²/h	197 m²/h	309 m²/h
	Production	31 m²/h	38 m²/h	88 m²/h	130m²/h	105 m²/h	165 m²/h	228 m²/h
	Quality	21 m²/h	26 m²/h	67 m²/h	94 m²/h	80 m²/h	114 m²/h	152 m²/h
Print Mode		Unidirectional & Bidirectional						
Media Ink								
Max. Print Width		1.6 m	2.5 m	3.2 m			5.2 m	
Max. Media Thickness		50 mm						
Media Type		Sheet Material: Signage, acrylic, metal sheets, PVC sheets, KT boards and more. Roll Material: Light sheets, soft films, car stickers, printed fabrics, knife-coated fabrics and more.						
Ink		Environmentally friendly UV / LED curable ink (VOC free)						
Ink Color		CMYK、Lc、Lm、W (Varnish optional)	CMYK、 Lc、 Lm、 W、 V			CMYK、 Lc、 Lm、 W		
Features								
UV Curing		LED						
Interface		USB						
RIP Support		Caldera / Onyx (Optional Purchase)						
Image Format		PDF, JPEG, TIFF, EPS, AI,etc.						
Dimension Weight								
Printer Size(L*W*H)		4.15*1.19*1.33 m	5.49*1.15*1.38 m	6.19*1.59*1.56 m		5.62*1.45*1.8 m	8.06*2.09*1.77 m	
Printer Net Weight		760 KG	1280 KG	2260 KG		2260 KG	4200 KG	
Printer Gross Weight		1170 KG	1875 KG	3130 KG		3330 KG	5400 KG	
Power Supply Environment								
Power Consumption		5.3 kW (27A)	8.3 kW (20A)			9.0 kW (20A)	13 kW (60A)	
Power Supply		230VAC 50Hz L/N/PE	400VAC 50Hz 3P/N/PE			220VAC 50Hz 1P/N/PE		
Environment		Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)						
Others		Requires ADP / Computer						

Industrial Digital Inkjet Printing Solution Provider


Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services





Shenzhen HandTop Tech Co.,Ltd
Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen
(2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)
Tel: +86 0755-23080896 / 23062862 **E-mail:** info@hanglorygroup.com
Fax: +86 0755-23217841 **Web:** www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation.
Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

HT3200UV

UV Hybrid Inkjet Printer

- Kyocera Series



*Illustration purpose

Optional Models:

- **HT1600UV** Easily competent for small and medium orders
- **HT2500UV** Cost-effective choice for coils and sheets in medium size
- **HT3200UV** Smart choice for large-format high-speed hybrid printing
- **HT3200EU** Brand new exterior design, suitable for wide-format hybrid printing
- **HT5200UV** Super large-format hybrid printing in one

Range of Large Format Printers with high speed drop on demand piezo inkjet technology.
Outstanding Performance:



Automatic Negative
Pressure System



Automatic Height
Measurement System



Adjustable UV
Curing Power



Sensitive Collision Avoidance
Device for the Carriage



Automatic Alignment
System (HT3200)



Adjustable Suction Area



Optional Anti-Static Bar



Positioning Rod



Integrated Software Functions
(Require ADP / Computer)



High-Quality Imported
Components

UV Hybrid Inkjet Printer - Kyocera Series								
Model		HT1600UV	HT2500UV	HT3200UV		HT3200EUV	HT5200UV	
Printing Information								
Printhead		Kyocera						
Number of Printhead		2-4 Pcs (1-Row)	3-4 Pcs (1-Row)	4-8 Pcs (2-Row)	4-15 Pcs (3-Row)	4-10 Pcs (Symmetrical 2-row)	2-15 Pcs (3-Row)	2-15 Pcs (Symmetrical 3-row)
Resolution		1200*1200 DPI				363*3600 DPI	1210*1200 DPI	363*3600 DPI
Production Mode	Draft	44 m ² /h	55 m ² /h	129 m ² /h	175 m ² /h	142 m ² /h	197 m ² /h	309 m ² /h
	Production	31 m ² /h	38 m ² /h	88 m ² /h	130m ² /h	105 m ² /h	165 m ² /h	228 m ² /h
	Quality	21 m ² /h	26 m ² /h	67 m ² /h	94 m ² /h	80 m ² /h	114 m ² /h	152 m ² /h
Print Mode		Unidirectional & Bidirectional						
Media Ink								
Max. Print Width		1.6 m	2.5 m	3.2 m			5.2 m	
Max. Media Thickness		50 mm						
Media Type		Sheet Material: Signage, acrylic, metal sheets, PVC sheets, KT boards and more. Roll Material: Light sheets, soft films, car stickers, printed fabrics, knife-coated fabrics and more.						
Ink		Environmentally friendly UV / LED curable ink (VOC free)						
Ink Color		CMYK、Lc、Lm、W (Varnish optional)	CMYK、Lc、Lm、W、V			CMYK、Lc、Lm、W		
Features								
UV Curing		LED						
Interface		USB						
RIP Support		Caldera / Onyx (Optional Purchase)						
Image Format		PDF, JPEG, TIFF, EPS, AI,etc.						
Dimension Weight								
Printer Size(L*W*H)		4.15*1.19*1.33 m	5.49*1.15*1.38 m	6.19*1.59*1.56 m		5.62*1.45*1.8 m	8.06*2.09*1.77 m	
Printer Net Weight		760 KG	1280 KG	2260 KG		2260 KG	4200 KG	
Printer Gross Weight		1170 KG	1875 KG	3130 KG		3330 KG	5400 KG	
Power Supply Environment								
Power Consumption		5.3 kW (27A)	8.3 kW (20A)			9.0 kW (20A)	13 kW (60A)	
Power Supply		230VAC 50Hz L/N/PE	400VAC 50Hz 3P/N/PE				220VAC 50Hz 1P/N/PE	
Environment		Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)						
Others		Requires ADP / Computer						

Industrial Digital Inkjet Printing Solution Provider


Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services





Shenzhen HandTop Tech Co.,Ltd
Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen
(2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)
Tel: +86 0755-23080896 / 23062862 **E-mail:** info@hanglorygroup.com
Fax: +86 0755-23217841 **Web:** www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation.
Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

V3.0/2025

HT3200UV

Inkjet UV Hybrid Printer

- Ricoh Series



*Illustration purpose

Optional Models:

- **HT1600UV** Easily competent for small and medium orders
- **HT2500UV** Cost-effective choice for coils and sheets in medium size
- **HT3200UV** Smart choice for large-format high-speed hybrid printing

Outstanding Performance:



Automatic Negative
Pressure System



Automatic Height
Measurement System



Adjustable UV
Curing Power



Sensitive Collision Avoidance
Device for the Carriage



Automatic Alignment
System (HT3200)



Adjustable Suction Area



Optional Anti-Static Bar



Positioning Rod



Integrated Software
Functions



High-Quality Imported
Components

Inkjet UV Hybrid Printer - Ricoh Series						
Model		HT1600UV	HT2500UV	HT3200UV		
Printing Information						
Printhead		GEN6				
Number of Printhead		2-8 Pcs N2-RowⅢ	4-8 Pcs N2-RowⅢ	4-8 Pcs N2-RowⅢ	4-8 Pcs N3-RowⅢ	2-16 Pcs N4-RowⅢ
Resolution		1200*1200 DPI		1210*1200 DPI		
Production Mode	Draft	52 m²/h	65 m²/h	74 m²/h	93 m²/h	108 m²/h
	Production	36 m²/h	44 m²/h	55 m²/h	80 m²/h	94 m²/h
	Quality	28倂/h	30 m²/h	40 m²/h	55 m²/h	68 m²/h
Print Mode		Unidirectional & Bidirectional				
Media Ink						
Max. Print Width		1.6 m	2.5 m	3.2 m		
Max. Media Thickness		50 mm				
Media Type		Sheet Material: Signage, acrylic, metal sheets, PVC sheets, KT boards and more. Roll Material: Light sheets, soft films, car stickers, printed fabrics, knife-coated fabrics and more.				
Ink		Environmentally friendly UV / LED curable ink (VOC free)				
Ink Color		CMYK♢Lc♢Lm♢W (Varnish optional)	CMYK♢Lc♢Lm♢W♢V			
Software Functions						
UV Curing		LED				
Interface		High Speed PCIE / USB				
RIP Support		Caldera				
Image Format		PDF, JPEG, TIFF, EPS, AI,etc.				
Dimension Weight						
Printer Size(L*W*H)		4.15*1.19*1.33 m	5.49*1.15*1.38 m		6.19*1.59*1.56 m	
Printer Net Weight		760 KG	1280 KG		2260 KG	
Printer Gross Weight		1170 KG	1875 KG		3130 KG	
Power Supply Environment						
Power Consumption		5.3 kW (27A)	8.3 kW (20A)		9.0 kW (20A)	
Power Supply		230VAC 50Hz L/N/PE	400VAC 50Hz 3P/N/PE			
Environment		Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)				
Others		Requires ADP / Computer				

Industrial Digital Printing Solution Provider


Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services





Shenzhen HandTop Tech Co.,Ltd
Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen
(2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)
Tel: +86 0755-23080896 / 23062862 **E-mail:** info@hanglorygroup.com
Fax: +86 0755-23217841 **Web:** www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation.
Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

V3.0/2025