

HT2500UV

UV Hybrid Inkjet Printer

- Kyocera Series



*Illustration purpose

Optional Models:

- **HT1600UV** Easily competent for small and medium orders
- **HT2500UV** Cost-effective choice for coils and sheets in medium size
- **HT3200UV** Smart choice for large-format high-speed hybrid printing
- **HT3200E** Brand new exterior design, suitable for wide-format hybrid printing
- **HT5200UV** Super large-format hybrid printing in one

Range of Large Format Printers with high speed drop on demand piezo inkjet technology.


Outstanding Performance:



Automatic Negative Pressure System



Automatic Height Measurement System



Adjustable UV Curing Power



Sensitive Collision Avoidance Device for the Carriage



Automatic Alignment System (HT3200)



Adjustable Suction Area



Optional Anti-Static Bar



Positioning Rod



Integrated Software Functions
(Require ADP / Computer)



High-Quality Imported Components

UV Hybrid Inkjet Printer - Kyocera Series

Model	HT1600UV	HT2500UV	HT3200UV	HT3200E	HT5200UV			
Printing Information								
Printhead	Kyocera							
Number of Printhead	2-4 Pcs (1-Row)	3-4 Pcs (1-Row)	4-8 Pcs (2-Row)	4-15 Pcs (3-Row)	4-10 Pcs (Symmetrical 2-row) 2-15 Pcs (3-Row)			
Resolution	1200*1200 DPI			363*3600 DPI	1210*1200 DPI 363*3600 DPI			
Production Mode	Draft	44 m ² /h	55 m ² /h	129 m ² /h	175 m ² /h	142 m ² /h	197 m ² /h	309 m ² /h
	Production	31 m ² /h	38 m ² /h	88 m ² /h	130 m ² /h	105 m ² /h	165 m ² /h	228 m ² /h
	Quality	21 m ² /h	26 m ² /h	67 m ² /h	94 m ² /h	80 m ² /h	114 m ² /h	152 m ² /h
Print Mode	Unidirectional & Bidirectional							
Media Ink								
Max. Print Width	1.6 m	2.5 m	3.2 m		5.2 m			
Max. Media Thickness	50 mm							
Media Type	Sheet Material: Signage, acrylic, metal sheets, PVC sheets, KT boards and more. Roll Material: Light sheets, soft films, car stickers, printed fabrics, knife-coated fabrics and more.							
Ink	Environmentally friendly UV / LED curable ink (VOC free)							
Ink Color	CMYK, Lc, Lm, W (Varnish optional)	CMYK, Lc, Lm, W, V		CMYK, Lc, Lm, W				
Features								
UV Curing	LED							
Interface	USB							
RIP Support	Caldera / Onyx (Optional Purchase)							
Image Format	PDF, JPEG, TIFF, EPS, AI, etc.							
Dimension Weight								
Printer Size(L*W*H)	4.15*1.19*1.33 m	5.49*1.15*1.38 m	6.19*1.59*1.56 m	5.62*1.45*1.8 m	8.06*2.09*1.77 m			
Printer Net Weight	760 KG	1280 KG	2260 KG	2260 KG	4200 KG			
Printer Gross Weight	1170 KG	1875 KG	3130 KG	3330 KG	5400 KG			
Power Supply Environment								
Power Consumption	5.3 kW (27A)	8.3 kW (20A)		9.0 kW (20A)	13 kW (60A)			
Power Supply	230VAC 50Hz L/N/PE	400VAC 50Hz 3P/N/PE		220VAC 50Hz 1P/N/PE				
Environment	Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)							
Others	Requires ADP / Computer							

Industrial Digital Inkjet Printing Solution Provider

<p>Independent printhead-drive technology</p> 	<p>Self-developed control system</p> 	<p>Self-developed MES system</p> 	<p>Independent ink industrial chain</p> 	<p>Remote service maintenance system and local services</p> 
---	--	--	---	---



Shenzhen HandTop Tech Co.,Ltd

Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen (2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)

Tel: +86 0755-23080896 / 23062862

E-mail: info@hanglorygroup.com

Fax: +86 0755-23217841

Web: www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation. Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

V3.0/2025

HT2500UV

UV Hybrid Inkjet Printer

- Ricoh Series



*Illustration purpose

Optional Models:

- **HT1600UV** Easily competent for small and medium orders
- **HT2500UV** Cost-effective choice for coils and sheets in medium size
- **HT3200UV** Smart choice for large-format high-speed hybrid printing

Range of Large Format Printers with high speed drop on demand piezo inkjet technology.


Outstanding Performance:



Automatic Negative Pressure System



Automatic Height Measurement System



Adjustable UV Curing Power



Sensitive Collision Avoidance Device for the Carriage



Automatic Alignment System (HT3200)



Adjustable Suction Area



Optional Anti-Static Bar



Positioning Rod



Integrated Software Functions
(Require ADP / Computer)



High-Quality Imported Components

UV Hybrid Inkjet Printer - Ricoh Series

Model	HT1600UV	HT2500UV	HT3200UV		
Printing Information					
Printhead	GEN6				
Number of Printhead	2-8 Pcs N2-Row	4-8 Pcs N2-Row	4-8 Pcs N2-Row	4-8 Pcs N3-Row	2-16 Pcs N4-Row
Resolution	1200*1200 DPI		1210*1200 DPI		
Production Mode	Draft	52 m ² /h	65 m ² /h	74 m ² /h	108 m ² /h
	Production	36 m ² /h	44 m ² /h	55 m ² /h	94 m ² /h
	Quality	28 倂/h	30 m ² /h	40 m ² /h	55 m ² /h
Print Mode	Unidirectional & Bidirectional				
Media Ink					
Max. Print Width	1.6 m	2.5 m	3.2 m		
Max. Media Thickness	50 mm				
Media Type	Sheet Material: Signage, acrylic, metal sheets, PVC sheets, KT boards and more. Roll Material: Light sheets, soft films, car stickers, printed fabrics, knife-coated fabrics and more.				
Ink	Environmentally friendly UV / LED curable ink (VOC free)				
Ink Color	CMYK+Lc+Lm+W (Varnish optional)	CMYK+Lc+Lm+W+V			
Features					
UV Curing	LED				
Interface	USB				
RIP Support	Caldera / Onyx (Optional Purchase)				
Image Format	PDF, JPEG, TIFF, EPS, AI, etc.				
Dimension Weight					
Printer Size(L*W*H)	4.15*1.19*1.33 m	5.49*1.15*1.38 m	6.19*1.59*1.56 m		
Printer Net Weight	760 KG	1280 KG	2260 KG		
Printer Gross Weight	1170 KG	1875 KG	3130 KG		
Power Supply Environment					
Power Consumption	5.3 kW (27A)	8.3 kW (20A)	9.0 kW (20A)		
Power Supply	230VAC 50Hz L/N/PE	400VAC 50Hz 3P/N/PE			
Environment	Separate workroom in cleaning and ventilated condition, avoid direct sunlight. Temperature:18-30°C(64-86 °F) Constant Humidity:30-70% (non-condensing)				
Others	Requires ADP / Computer				

Industrial Digital Inkjet Printing Solution Provider

<p>Independent printhead-drive technology</p> 	<p>Self-developed control system</p> 	<p>Self-developed MES system</p> 	<p>Independent ink industrial chain</p> 	<p>Remote service maintenance system and local services</p> 
---	--	--	---	---



Shenzhen HandTop Tech Co.,Ltd

Add: No.39 Qingfeng Road, Baolong Street, Longgang District, Shenzhen
(2-3/F, Building C, Jingmida Digital Culture Industry Park - HanGlory Group)

Tel: +86 0755-23080896 / 23062862

E-mail: info@hanglorygroup.com

Fax: +86 0755-23217841

Web: www.hanglorygroup.com/en

© The above information is for reference only. Shenzhen HandTop Tech Co.,Ltd. reserves the right of final interpretation.
Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.

V3.0/2025